



NOTES:

1. SOLVENT WELD ALL JOINTS. (NON GASKETED)
2. WHEN SANITARY SEWER SERVICE IS NOT ACCOMPANIED BY A WATER SERVICE IN THE SAME TRENCH, INSTALL A HEAVY METAL TEE POSTS FROM INVERT TO 3' ABOVE FINISHED GRADE AND PAINT TOP 6" OF POST FLUORESCENT GREEN PAINT.
3. CLEANOUT REQUIRED ON PRIVATE PROPERTY IF DISTANCE FROM MAIN TO HOUSE EXCEEDS 90 FEET.
4. ALL PIPE SHALL BE BEDDED ON GRANULAR BEDDING (3149.2-F) OR COURSE FILTER AGGREGATE (3149.2-H).
5. INSTALL TRACER WIRE SYSTEM PER SPEC'S - DETAIL PLATE 5507.
6. WHEN A SIDEWALK OR TRAIL IS PRESENT IN THE BLVD. THE SERVICE MAY BE EXTENDED INTO THE D&U EASEMENT WITH THE CITY ENGINEERS APPROVAL.



**CITY OF
CHANHASSEN**

TYPICAL SANITARY
SEWER SERVICE
(LESS THAN 16' DEEP)

REVISED: 11-19

FILE NAME: G:\ENG\SPCS\2001

ENGINEERING DEPARTMENT

PLATE NO.:

2001